

ZCKE61TK

Glava omejitvenega stikala ZCKE - bat s kovinskim zaključkom



Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJD37H7 ZCKJD35H7 ZCKJ8 ZCKJ11H7 ZCKJD31H7 ZCKJ7H29 ZCKJ2H29 ZCKJ41 ZCKJ7H7 ZCKJ11H29 ZCKJ2 ZCKJ4H29 ZCKJ8H29 ZCKJD35H29 ZCKJ1 ZCKJ2H7 ZCKJD39H7 ZCKJ7 ZCKJ4H7 ZCKJ5H29 ZCKJD31 ZCKJ1H29 ZCKJ9H7 ZCKJD37 ZCKJD35 ZCKJD37H29 ZCKJ21 ZCKJ5H7 ZCKJ21H7 ZCKJD31H29 ZCKJD39H29 ZCKJ41H7 ZCKJ41H29 ZCKJ21H29 ZCKJ1H7 ZCKJ6 ZCKJ9 ZCKJ8H7 ZCKJ11 ZCKJ4 ZCKJD39 ZCKJ6H29 ZCKJ5 ZCKJ9H29 ZCKJ6H7
Gibanje operativne glave	Linearno
Tip upravljanja	Zaključni bat Povratna vzmet Kovinski
Tip pristopa	Vertikalni pristop, 1 smer

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Komplementarno

Stikalno aktiviranje	Na koncu
Pozitivna odprtina	Z
Material glave	Kovinski

Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Korozivni

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	140 G
Višina embalaže 1	4 Cm
Širina embalaže 1	4,5 Cm
Dolžina embalaže 1	8,5 Cm

Offer Sustainability

Uredba REACH	Izjava REACH
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------