

## ZCKE625

Glava omejitvenega stikala ZCKE - jekleni  
valjni bat - +120 °C



### Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJ7H29 ZCKJ7 ZCKJ4H29 ZCKJ4H7 ZCKJ11 ZCKJD31H29 ZCKJD37 ZCKJD37H29 ZCKJ8 ZCKJ9H7 ZCKJD35H7 ZCKJD35H29 ZCKJ21 ZCKJD31H7 ZCKJ8H29 ZCKJD39H7 ZCKJD35 ZCKJ1 ZCKJ2H7 ZCKJ21H7 ZCKJ21H29 ZCKJ4 ZCKJD31 ZCKJ41H7 ZCKJ11H7 ZCKJ9H29 ZCKJ5H29 ZCKJ5 ZCKJ2 ZCKJ11H29 ZCKJD39 ZCKJ1H29 ZCKJ41 ZCKJ6H29 ZCKJ41H29 ZCKJ2H29 ZCKJ8H7 ZCKJ6 ZCKJ7H7 ZCKJ9 ZCKJD39H29 ZCKJ1H7 ZCKJ6H7 ZCKJ5H7 ZCKJD37H7
Gibanje operativne glave	Linearno
Tip upravljanja	Valjasti bat Povratna vzmet Kovinski
Tip pristopa	Bočni pristop, 2 smeri

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Teža izdelka	0,155 Kg
Material glave	Kovinski

## Okolje

Temperatura okoliškega zraka za delovanje	10...120 °C
Temperatura okoliškega zraka za skladiščenje	10...120 °C
Okoljske značilnosti	Visoka temperatura

## Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	153 G
Višina embalaže 1	4 Cm
Širina embalaže 1	4,5 Cm
Dolžina embalaže 1	8,7 Cm

## Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------