

ZCKE636

Glava omejitvenega stikala ZCKE - stranski kovinski bat - -40 °C



Glavno

Serijski izdelki	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJD39H7 ZCKJD37H29 ZCKJ8 ZCKJ5 ZCKJ6H29 ZCKJ7 ZCKJ5H7 ZCKJ1H29 ZCKJ2 ZCKJ8H29 ZCKJ21H29 ZCKJ5H29 ZCKJ7H29 ZCKJ6H7 ZCKJD31H29 ZCKJD39 ZCKJ2H7 ZCKJ1 ZCKJD31 ZCKJ11 ZCKJ2H29 ZCKJ21H7 ZCKJ9H29 ZCKJD35H7 ZCKJD37H7 ZCKJ11H7 ZCKJ7H7 ZCKJD35 ZCKJ8H7 ZCKJ21 ZCKJ9 ZCKJ9H7 ZCKJ6 ZCKJ1H7 ZCKJD37 ZCKJD35H29 ZCKJD31H7 ZCKJD39H29 ZCKJ11H29
Gibanje operativne glave	Linearno
Tip upravljanja	Stranski bat Povratna vzmet Kovinski
Tip pristopa	Bočni pristop, 1 smer

Komplementarno

Stikalno aktiviranje	Na koncu
Pozitivna odprtina	Z
Teža izdelka	0,2 Kg
Material glave	Kovinski

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Okolje

Temperatura okoliškega zraka za delovanje	-40...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Nizka temperatura

Packing Units

Teža embalaže 1	0,200 Kg
Višina embalaže 1	0,300 Dm
Širina embalaže 1	0,640 Dm
Dolžina embalaže 1	1,080 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------