


ZCKE66

Glava omejitvenega stikala ZCKE - jekleni valj s krogličnim ležajem



ZCK E66

Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJD39 ZCKJ6H29 ZCKJ9H29 ZCKJ8 ZCKJ5H7 ZCKJD37H29 ZCKJ2H7 ZCKJ41 ZCKJ1 ZCKJD31H7 ZCKJ21 ZCKJ5 ZCKJD35H7 ZCKJ2 ZCKJD39H29 ZCKJ7 ZCKJ2H29 ZCKJ8H29 ZCKJ41H7 ZCKJ4H7 ZCKJ9 ZCKJ11H7 ZCKJ6 ZCKJ8H7 ZCKJ11H29 ZCKJ9H7 ZCKJ1H29 ZCKJ1H7 ZCKJ5H29 ZCKJD35H29 ZCKJD31H29 ZCKJ6H7 ZCKJD37 ZCKJ41H29 ZCKJ4H29 ZCKJD39H7 ZCKJ21H7 ZCKJ7H29 ZCKJD35 ZCKJD37H7 ZCKJ7H7 ZCKJD31 ZCKJ21H29 ZCKJ4 ZCKJ11
Gibanje operativne glave	Linearno
Tip upravljanja	Zaključni bat Povratna vzmet Kovinski Pritrjeno s krogličnim ležajem)
Tip pristopa	Večstranski pristop

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Material glave	Kovinski

Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Standard

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	147 G
Višina embalaže 1	4,2 Cm
Širina embalaže 1	4,7 Cm
Dolžina embalaže 1	8,6 Cm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------