


## ZCKE665

Glava omejitvenega stikala ZCKE - jekleni valj s krogličnim ležajem - +120 °C



**ZCK E66**

### Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJD39H29 ZCKJ41 ZCKJ11H29 ZCKJ41H29 ZCKJ6 ZCKJ1H7 ZCKJ5H7 ZCKJ5 ZCKJ6H29 ZCKJD35H7 ZCKJ8H29 ZCKJ21H7 ZCKJD39 ZCKJ21 ZCKJ4 ZCKJ9H7 ZCKJD31H29 ZCKJD37H29 ZCKJ1 ZCKJ21H29 ZCKJ1H29 ZCKJ2 ZCKJD37 ZCKJ4H29 ZCKJD35 ZCKJD39H7 ZCKJ5H29 ZCKJD31H7 ZCKJ2H7 ZCKJD37H7 ZCKJD35H29 ZCKJ7 ZCKJ7H29 ZCKJ8 ZCKJ2H29 ZCKJ8H7 ZCKJ4H7 ZCKJ7H7 ZCKJ6H7 ZCKJ41H7 ZCKJD31 ZCKJ9 ZCKJ9H29 ZCKJ11H7 ZCKJ11
Gibanje operativne glave	Linearno
Tip upravljanja	Zaključni bat Povratna vzmet Kovinski Pritrjeno s krogličnim ležajem)
Tip pristopa	Večstranski pristop

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Teža izdelka	0,15 Kg
Material glave	Kovinski

## Okolje

Temperatura okoliškega zraka za delovanje	10...120 °C
Temperatura okoliškega zraka za skladiščenje	10...120 °C
Okoljske značilnosti	Visoka temperatura

## Packing Units

Teža embalaže 1	0,150 Kg
Višina embalaže 1	0,041 Dm
Širina embalaže 1	0,045 Dm
Dolžina embalaže 1	0,085 Dm

## Offer Sustainability

Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------