

## Product data sheet

### Characteristics

# ZCKY46

Vzvod omej. stik. ZCKY - kovinski vzvod valja s spr. dolžino - -40 do 120 °C



### Glavno

Serijski izdelek	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Vzvod/Ročica mejnega stikala
Kratko ime naprave	ZCKY
Združljivost izdelkov	XCKT XCKP
Povezana glava	ZCKE05 ZCKD05
Gibanje operativne glave	Vrtljiv
Tip upravljanja	Valj ročice Povratna vzmet Kovinski Spremenljiva dolžina)
Tip pristopa	Bočni pristop

### Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Brez

### Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C Standard -40...70 °C Nizka temperatura 10...120 °C Visoka temperatura
Temperatura okoliškega zraka za skladiščenje	-40...70 °C Standard -40...70 °C Nizka temperatura 10...120 °C Visoka temperatura
Okoljske značilnosti	Nizka temperatura Standard Visoka temperatura

### Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	35 G
Višina embalaže 1	2 Cm
Širina embalaže 1	3 Cm
Dolžina embalaže 1	10 Cm
Tip enote v embalaži 2	S01
Število enot v embalaži 2	10
Teža embalaže 2	398 G
Višina embalaže 2	15 Cm
Širina embalaže 2	15 Cm
Dolžina embalaže 2	40 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------