

Product data sheet

Characteristics

ZCMC25L3

Predhodno kabliran priključek ZCMC - 2 pola -
PvR - 3 m



Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Izdelek ali sestavni del	Pred-kabelska povezava
Ime komponente	ZCMC
Povezano ohišje	ZCMD25
Število polov	2
Tip kontakta in sestava	1 NC + 1 NO
Premik kontakta	Slow-break, break before make

Komplementarno

Združljivost izdelkov	XCMD25
Električna povezava	Cable
Dolžina kabla	3 M
Material izolacije žice	PvR

Packing Units

Teža embalaže 1	0,275 Kg
Višina embalaže 1	0,200 Dm
Širina embalaže 1	1,700 Dm
Dolžina embalaže 1	2,000 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe

Pogodbena garancija

Garancija	18 months
-----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.