

## Product data sheet

### Characteristics

# ZCMC39L1

Predhodno kabliran priključek ZCMC - 3 poli -  
PvR - 1 m



### Glavno

|                          |  |
|--------------------------|--|
| Serija izdelka           | Telemecanique Limit switches XC Standard |
| Izdelek ali sestavni del | Pred-kabelska povezava                   |
| Ime komponente           | ZCMC                                     |
| Povezano ohišje          | ZCMD39                                   |
| Število polov            | 3  |
| Tip kontakta in sestava  | 2 NC + 1 NO                              |
| Premik kontakta          | Hitro ukrepanje                          |

### Komplementarno

|                         |        |
|-------------------------|--------|
| Združljivost izdelkov   | XCMD39 |
| Električna povezava     | Cable  |
| Dolžina kabla           | 1 M    |
| Material izolacije žice | PvR    |

### Packing Units

|                    |          |
|--------------------|----------|
| Teža embalaže 1    | 0,108 Kg |
| Višina embalaže 1  | 0,200 Dm |
| Širina embalaže 1  | 1,500 Dm |
| Dolžina embalaže 1 | 1,200 Dm |

### Offer Sustainability

|                                |  |
|--------------------------------|--|
| Status trajnostne ponudbe      | Izdelek Green Premium  |
| Uredba REACH                   | <a href="#">Izjava REACH</a>   |
| Direktiva EU ROHS              | Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Brez živega srebra             | Da   |
| Informacije o izvzetju iz RoHS | <a href="#">Da</a>   |
| Razkritje okoljskih podatkov   | <a href="#">Okoljski Profil Izdelka</a>  |
| Profil krožnega gospodarstva   | <a href="#">Informacije O Izteku Življenjske Dobe</a>  |

### Pogodbena garancija

|           |           |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.